



RECOMMENDED
CABLE STRIPPING DIM'S



Die Size B



Die Size A



Max-Gain Systems, Inc.
150 Dodd Street SE, Marietta, GA, 30060
Phone: (770) 973-6251 | Fax: (678) 401-3854
Website: www.mgs4u.com | E-Mail: sales@mgs4u.com

TITLE: Type N female Crimp Connector for RG-223, RG-59, RG-316,
LMR-240, RG-8X mini 8, and other 0.240 Inch OD Coax

DRAWING NO: 7306-N-8X
FILE NO :

NO.	DESCRIPTION	MATERIAL	FINISH	QTY	UNLESS OTHERWISE SPECIFIED TOLERANCES			PART NO	DATE
					0.5-5 = ±0.2	5-30 = ±0.4	30-120 = ±0.6		
1	FERRULE	BRASS	SILVER	1	120-315 = ±1	315-1000 = ±1.6	1000-2000 = ±2.4	APPROVED	DATE
1	PIN	BRASS	GOLD	1				CHECKED	DATE
1	INSULATOR	TEFLON	WHITE	1				DRAWN	DATE
1	BODY	BRASS	SILVER	1					
	NO. DESCRIPTION	MATERIAL	FINISH	QTY	UNIT: mm		SCALE: .		