



150 Dodd Street SE
Marietta, GA. 30060

Phone: 770-973-6251
Fax: 678-401-3854

Email: info@mgs4u.com
Website: www.mgs4u.com

Type N female to RP-TNC male Adapter



Technical Data Sheet

This Type N female to RP-TNC male adapter is one of several thousand RF products available from Max-Gain Systems, Inc. This adapter is a between series coaxial adapter.

This adapter is made from a Solid Brass body that is precision machined and plated with Nickel for superior performance and value. This Type N female to RP-TNC male adapter has a Delrin dielectric and a gold plated brass center pin. The Type N female side accepts a Type N male which contains a gasket, for shock- / vibration- resistant and waterproof connections. The RP-TNC male side provides the jack that is normally found in a TNC female connection and internal threads, RP-TNC connections are popular in wireless and Wi-Fi applications.

Material Specifications

Type N female to RP-TNC male Adapter

Part Number 8905

Description	Material	Plating
Insulator	Delrin	White
Pin	Brass	Gold
Body	Brass	Nickel

Mechanical Specifications

Size	Dimension
Length	1.48 in (37.5 mm)
Width	0.67 in (17 mm)
Height	0.67 in (17 mm)
Weight	1.3 oz (38 g)

Environmental Specifications

Temperature	Spec
Operating Range	-65 to +165 deg C

Compliance Certifications (see product page for current documentation)

Availability Click the following link (or enter part number in the “SEARCH” bar at the top of any page of the website) to obtain additional part information including price, inventory and certifications: <https://mgs4u.com/product/type-n-female-to-rp-tnc-male-adapter-8905/>

