

150 Dodd Street SE Marietta, GA. 30060

Phone: 770-973-6251 Fax: 678-401-3854 Cage Code: 7JZZ8 Email: <u>info@mgs4u.com</u> Website: <u>www.mgs4u.com</u>

SMA female 4-Hole Panel Mount Solder Connector



Technical Data Sheet

This SMA Female 4-Hole Panel Mount Solder Connector is one of several thousand RF products available from Max-Gain Systems, Inc.

This connector is made from a Solid Brass body that is precision machined and plated with Gold for superior performance and value. This SMA Female 4-Hole Panel Mount Solder Connector has a PTFE dielectric and a gold plated brass center pin. The SMA female provides a jack and exterior threads enabling a sub-miniature and tight-locking connection for use at higher frequencies.

Material Specifications

SMA female 4-Hole Panel Mount Solder Connector		Part Number 7814
Description	Material	Plating
Pin	Phosphor Bronze	Gold
Insulator	PTFE	White
Body	Brass	Gold

Electrical Specifications

Criteria	Dimension
Impedance (Nominal)	50 Ohms
Frequency Range	DC to 18 GHz
Working Voltage	335

Mechanical Specifications

Size	Dimension
Length	0.58 in (14.65 mm)
Width	0.5 in (12.7 mm)
Height	0.5 in (12.7 mm)
Weight	0.1 oz (3 g)

Environmental Specifications

Temperature	Spec
Operating Range	-65 to +165 deg C

Compliance Certifications (see product page for current documentation)

Availability Click the following link (or enter part number in the "SEARCH" bar at the top of any page of the website) to obtain additional part information including price, inventory and certifications: <u>https://mgs4u.com/product/sma-female-4-hole-panel-mount-solder-connector-for-0-100-inch-od-coax-7814/</u>

